KIA MOTORS CORPORATION

EXECUTIVE ORDER A-315-0059

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		COMPI (*=N/A or A/E=ext	EDIATE JSE LIANCE full in-use; 1. / evap. ate in-use)	FUEL TYPE
			USEPA Bin 4	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2
2006	6KMXV02.0LW4	Passenger Car	Counted as ARB LEV2 ULEV	120K	150K	*	E	Unleaded)
No.	ECS &	SPECIAL FEATURES	EVAPORATIVE		AF)		DISPLAC	EMENT (L)
1	WU-TWC,Τ\	NC, H02S(2), SFI, OBD(F)	6KMXR	0110PDL		- 4		
•	•			<u>* </u>	- 3		2	
•				*	41			
•		*	See .	*				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50⁰ Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _______day of June 2005.

Hen Lyons, Chief

Mobile Source Operations Division

KIA MOTORS CORPORATION

EXECUTIVE ORDER A-315-0059

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ RAF=* AVERAGE [g/mi] CH4 RAF = *		NMOG or	CH4=methane: NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram										
CERT	STD	NMOG	NMHC	NMHC	not-soak; RL [g/mij=running loss; Okvk [g/gallon dispensed]-on-board relidening vapor recovery, g-gram, ing-miling ml-mile; K=1000 miles; F-degrees Fahrenheit; SFTP-supplemental federal test procedure									316111
0.042	CERT CERT		[g/mi]	CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
0.043	0.046	[g/mi]	[g/mi]	[8,,,,,]	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
100	@ 50K	*	*	*	•	*	*	*	* .	*	+	*	*	*
1.00	@ UL	0.029	*	0.070	0.2	2.1	0.003	0.04	1.0	11.	*	*	0.001	0.05
(A) (A) (B)	50°F & 4K	*	*	*	*	*	*	*	*	*	*	*	•	*

CO [g/mi]				Ox [g/mi] oosite)		g/mi] oosite)		:+NOx [US06]	co [NMHC [g/mi]] 00 [80	
	0°F & 50K	1.7 ENW - 1	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	1.6	SFTP @ 4000 miles	*	*	*	*	0.06	0.14	5.0	8.0	0.03	0.20	0.7	2.7
STD	10.0	SFTP @ 120000 miles	0.05	0.63	2.14	3.47	*	*	*	*	*	*	*	*

Evaporative Family	3-Days Diurna (grams/te		2-Days Diurn (grams/te	al + Hot Soak est) @ UL	Runnin (grams/m		On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
6KMXR0110PDL	0.26	0.50	0.27	0.65	0.01	0.05	0.02	0.20	
*	*	*	*	*	*	*	*	*	
*	*	*	*	*	*	*	*	*	
*		*	*	*	*	*	*	*	

^{* =} not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air-fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2006 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN-U COMPU (*=N/A or t	IANCE full in-use; n. / evap.	PHASE-IN STD.	OBD II
					EXH	EVAP		
KIA	SPECTRA	6KMXR0110PDL	1	2	*	E	SFTP	Full